



GS BATTERY – CANADA

6 ANTARES DRIVE . NEPEAN . ONTARIO . K2E 8A9

PHONE: (613) 228-5000 FAX: (613) 228-0098

PORTALAC

SUPERLAC

Rechargeable Sealed Lead-Acid (VRLA) Batteries

Model	Nominal Voltage	Capacity (20 Hour)	Length	Width	Height (Case)	Height (Terminal)	KG	Terminal
PE6V1.2F1	6	1.2	98	24	51	55	0.30	F1: Amp Faston Type 187
PE6V3AF1	6	3	134	34	60	64	0.68	F1: Amp Faston Type 187
PE6V3.2F1	6	3.2	66	33	119	124	0.75	F1: Amp Faston Type 187
PE6V4.5F1	6	4.5	70	47	102	106	0.89	F1: Amp Faston Type 187
PE6V7.2F1	6	7.2	151	34	94	98	1.38	F1: Amp Faston Type 187
PE6V8F1	6	8	98	56	118	118	1.52	F1: Amp Faston Type 187 (Position: F1)
PE6V8F4	6	8	98	56	118	118	1.52	F1: Amp Faston Type 187 (Position: F4)
PE6V12F1	6	12	151	51	94	98	2.10	F1: Amp Faston Type 187
PE6V12F2	6	12	151	51	94	98	2.10	F2: Amp Faston Type 250
PE12V1.2F1	12	1.2	97	42	51	55	0.55	F1: Amp Faston Type 187
PE12V2.2F1	12	2.2	178	34	60	64	0.98	F1: Amp Faston Type 187
PE12V2.7F1	12	2.7	79	55	102	106	1.10	F1: Amp Faston Type 187
PE12V3AF1	12	3	134	68	61	65	1.30	F1: Amp Faston Type 187
PE12V4.5F1	12	4.5	90	70	102	106	1.75	F1: Amp Faston Type 187
PX12050-SHR	12	5	90	70	102	106	2.00	F2: Amp Faston Type 250
PE12V7.2F1	12	7.2	151	65	94	98	2.75	F1: Amp Faston Type 187
PE12V7.2F2	12	7.2	151	65	94	98	2.75	F2: Amp Faston Type 250

Click on a **Model Number** to retrieve the Specification Data sheet from the Internet (PDF format)

Page 1 of 2

Click here to retrieve the PDF Catalogue which contains all models listed in this document (2.3 MB)

Click here to retrieve the Material Safety Data Sheet (MSDS) from the Internet (PDF format)



GS GS BATTERY – CANADA

6 ANTARES DRIVE . NEPEAN . ONTARIO . K2E 8A9

PHONE: (613) 228-5000 FAX: (613) 228-0098

PORTALAC

SUPERLAC

Rechargeable Sealed Lead-Acid (VRLA) Batteries

Model	Nominal Voltage	Capacity (20 Hour)	Length	Width	Height (Case)	Height (Terminal)	KG	Terminal
PE12V9F2	12	9	151	65	112	116	3.30	F2: Amp Faston Type 250
PE12V12F2	12	12	151	98	94	98	4.35	F2: Amp Faston Type 250
PE12V17B1	12	17	181	76	167	167	6.70	B1: M5 Bolt & Nut type
PE12V18B1	12	18	181	76	167	167	6.45	B1: M5 Bolt & Nut type
PE12V24AB1	12	24	175	166	125	125	9.40	B1: M5 Bolt & Nut type
PE12V40B2	12	40	196	163	174	174	14.00	B2: M6 Bolt & Nut type
SE50-12	12	50	299	128	201	201	18.00	Threaded Post (M6)
SE65-12	12	65	363	128	201	201	22.00	Threaded Post (M6)

Click on a **Model Number** to retrieve the Specification Data sheet from the Internet (PDF format)

Page 2 of 2

Click here to retrieve the PDF Catalogue which contains all models listed in this document (2.3 MB)

Click here to retrieve the Material Safety Data Sheet (MSDS) from the Internet (PDF format)