




PK12V2APC

RECHARGEABLE SEALED LEAD ACID (VRLA) BATTERY

Nominal Voltage 12 Volt

20 Hour Rate Capacity 2 Ah



Dimensions	Inches	mm
Length	5.91	150
Width	0.79	20
Case Height	3.54	90
Terminal Height	3.54	90
[See Drawing for Tolerances]		
Weight (Approx.)	Lbs.	Kg
	1.656	0.751

Case Material A.B.S. (UL94-HB)

Terminal Faston Type 187 (F1) & Pressure Contact

Maximum Short Duration Discharge Current	
(5 Seconds or Less)	30 Amperes
(10 Seconds or Less)	20 Amperes
(60 Seconds or Less)	12 Amperes

Internal Resistance (Fully Charged Battery)
(Approximately) 45 mOhm

Energy Density (@ 20 Hour Rate)
1.46 Watt-Hours/Cubic Inch (88.89 Watt-Hours/Litre)


Specific Energy (@ 20 Hour Rate)
14.5 Watt-Hours / Pound (31.96 Watt-Hours / Kg)

Operating Temperature Range	
Discharge	-4°F (-20°C) ~ 122°F (50°C)
Recharge	32°F (0°C) ~ 104°F (40°C)
Storage	-20°C (-4°F) ~ 40°C (104°F)

Self Discharge Rate
About 3% / Month @ 68~77°F (20~25°C)

Constant Current Discharge Characteristics at 77°F (25°C)

Discharge Hours	Discharge Amperes	Capacity in Ah's	Final Voltage	Discharge C-Rate
20	0.10	2.00	10.50	0.05
10	0.18	1.80	10.50	0.09
5	0.34	1.70	10.20	0.17
4	0.40	1.60	10.20	0.20
Minutes				
60	1.20	1.20	9.48	0.6
31	2.00	1.04	9.00	1.0
7	6.00	0.70	6.00	3.0



Recharge Method : Connect battery to a Current Limited, Constant Voltage Source.


- Limit the Initial Recharge Current to 500 mA or less.
- To promote satisfactory performance in Cyclic Applications, a minimum Recharge Current of 200 mA is recommended.
- Employ Charge Voltage Temperature Compensation when Battery Temperature is less than 50°F (10°C) or greater than 86°F (30°C). Use the **Recommended** Voltage and Normalize to 77°F (25°C).
- The use of Compensation through the whole Temperature range is not generally necessary, but doing so may optimize Service Life.
- If the **Recommended** Recharge voltage is used, no Temperature Compensation is required within the range of 50~86°F (10~30°C).


Cyclic Application Recharge Voltage (77°F / 25°C)

Minimum	Recommended	Maximum	
14.40	14.55	14.70	Volts D.C.
2.40	2.425	2.45	Per Cell
Temperature Coefficient: -2.8mV/°F/Cell (- 5mV/°C/Cell)			

Standby Application Recharge Voltage (77°F / 25°C)

Minimum	Recommended	Maximum	
13.50	13.65	13.80	Volts D.C.
2.25	2.275	2.30	Per Cell
Temperature Coefficient: -1.7mV/°F/Cell (- 3mV/°C/Cell)			



Peak Energy Products PK Series			
Rechargeable Sealed Lead-Acid (VRLA) Battery			
Model:	PK12V2A		
Voltage:	12	Capacity:	2 Ah (20 Hr)
Terminal:	Faston 187 (F1) & Pressure Contact		
Dimensions:	mm (Inch)		
Drawing:	PK12V2AT-0110CE		
Date:	2001.10.25		
© Peak Energy Products			
DO NOT SCALE DRAWING			

