



PK12V3F1

RECHARGEABLE SEALED LEAD ACID (VRLA) BATTERY

Nominal Voltage 12 Volt

20 Hour Rate Capacity 3 Ah



Dimensions	Inches	mm
Length	5.28	134
Width	2.64	67
Case Height	2.34	60
Terminal Height	2.58	66

[See Drawing for Tolerances]

Weight (Approx.)	Lbs.	Kg
	3.10	1.41

Case Material A.B.S. (UL94-HB)

Terminal Faston Type 187 (F1)

Maximum Short Duration Discharge Current	
(5 Seconds or Less)	45 Amperes
(10 Seconds or Less)	30 Amperes
(60 Seconds or Less)	18 Amperes

Internal Resistance (Fully Charged Battery)
(Approximately) 40 mOhm

Energy Density (@ 20 Hour Rate)
1.1 Watt-Hours/Cubic Inch (67.39 Watt-Hours/Litre)


Specific Energy (@ 20 Hour Rate)
11.61 Watt-Hours / Pound (25.59 Watt-Hours / Kg)

Operating Temperature Range	
Discharge	-4°F (-20°C) ~ 122°F (50°C)
Recharge	32°F (0°C) ~ 104°F (40°C)
Storage	-4°F (-20°C) ~ 104°F (40°C)

Self Discharge Rate
About 3% / Month @ 68~77°F (20~25°C)

Constant Current Discharge Characteristics at 73.4°F (23°C)

Discharge Time	Discharge Amperes	Capacity in Ah's	Final Voltage	Discharge C-Rate
20.0 Hrs	0.15	3.00	10.50	0.05
9.2 Hrs	0.30	2.77	10.50	0.10
5.0 Hrs	0.51	2.54	10.29	0.17
4.1 Hrs	0.60	2.44	10.20	0.20
2.1 Hrs	1.05	2.23	9.94	0.35
64.0 Mins	1.8	1.92	9.54	0.6
32.5 Mins	3.0	1.62	9.00	1.0
7.2 Mins	9.0	1.08	6.00	3.0



Recharge Method : Connect battery to a Current Limited, Constant Voltage Source.

- Limit the initial recharge current to 750 mA or less.
- To promote satisfactory performance in Cyclic applications, a minimum recharge current of 300 mA is recommended.
- Employ Charge Voltage Temperature Compensation when battery temperature is less than 50°F (10°C) or greater than 86°F (30°C). Use the **Recommended** voltage and normalize to 77°F (25°C).
- The use of compensation through the whole temperature range is not generally necessary, but doing so may optimize service life.
- If the **Recommended** recharge voltage is used, no Temperature Compensation is required within the range of 50~86°F (10~30°C).

Cyclic Application Recharge Voltage (77°F / 25°C)

Minimum	Recommended	Maximum	
14.40	14.55	14.70	Volts D.C.
2.40	2.425	2.45	Per Cell


Temperature Coefficient: -2.8mV/°F/Cell (-5mV/°C/Cell)

Standby Application Recharge Voltage (77°F / 25°C)

Minimum	Recommended	Maximum	
13.50	13.65	13.80	Volts D.C.
2.25	2.275	2.30	Per Cell

Temperature Coefficient: -1.7mV/°F/Cell (-3mV/°C/Cell)



PEAK Energy Products PK Series		
Rechargeable Sealed Lead-Acid (VRLA) Battery		
Model:	PK12V3	
Voltage:	12	Capacity: 3 Ah (20 Hr)
Terminal:	Faston Type 187 (F1)	
Dimensions:	mm (Inch)	
Drawing:	PK12V3T-0905CE	
Date:	2009.05.07	
© Peak Energy Products		
DO NOT SCALE DRAWING		

