

DOWNLOAD CATALOGUE



LED MR16 GU5.3 Base 12V AC/DC

| Nominal Wattage | Overdrive Model # | Item Description & CCT | Initial Lumen | Lumen Per Watt | Beam Angle | СВСР | Av Rated Life (hrs.) | Diameter inch / mm | Length Inches / mm | Pack Master | ltem # |
|--------------------|----------------------|--|------------------|-------------------|---------------|------|-----------------------------|--------------------------|--------------------------|----------------|--------|
| 4.5W | L4MR16BS/NFL/30K | 4.5W LED MR16 Warm White Narrow Flood | 285 | 64 | 22° | 1250 | 35,000 | 1.97 / 50 | 1.94 /49.3 | 48 | 508 |
| 4.5W | L4MR16BS/FL/30K | 4.5W LED MR16 Warm White Flood | 270 | 60 | 36° | 560 | 35,000 | 1.97 / 50 | 1.94 /49.3 | 48 | 509 |

LED MR16 GU5.3 Base 12V AC/DC

| Nominal Wattage | Overdrive Model # | Item Description & CCT | Initial Lumen | Lumen Per Watt | Beam Angle | CBCP | Av Rated Life (hrs.) | Diameter inch / mm | Length Inches / mm | Pack Master | ltem # |
|--------------------|----------------------|---|------------------|-------------------|---------------|------|-----------------------------|-----------------------|--------------------------|----------------|--------|
| 4.5W | L4MR16BS/WFL/30K | 4.5W LED MR16 Warm White Wide Flood | 240 | 54 | 48° | 300 | 35,000 | 1.97 / 50 | 1.94 /49.3 | 48 | 510 |
| 4.5W | L4MR16BS/NFL/50K | 4.5W LED MR16 Day Light Narrow Flood | 315 | 70 | 22° | 1390 | 35,000 | 1.97 / 50 | 1.94 /49.3 | 48 | 511 |
| 4.5W | L4MR16BS/FL/50K | 4.5W LED MR16 Day Light Flood | 300 | 67 | 36° | 600 | 35,000 | 1.97 / 50 | 1.94 /49.3 | 48 | 512 |
| 4.5W | L4MR16BS/WFL/50K | 4.5W LED MR16 Day light Wide Flood | 265 | 59 | 48° | 330 | 35,000 | 1.97 / 50 | 1.94 /49.3 | 48 | 513 |

Advance COB LED Benefits & Features

Uses COB (Chip on Board) Advanced ceramic substrate LED provides: Excellent Color Consistency and maintenance.

Higher Reflectivity and Extra Safety due to use of Ceramic Substrate.

Intelligently and aesthetically designed & Longer Life due to higher life of Ceramic Substrate.

Intelligently and aesthetically designed

No Shadowing effecting like Multiple LED MR16 Bulbs.and Uniform Spread of light.


Designed for long product life - electronics / LEDs and Instantly bright and color stability over lifetime of product.

Environment friendly - mercury free and lead free and Maintenance free for more than ten years (assuming 8 hours per day 365 days per year)

Significantly reduces maintenance costs and Low energy consumption Save up to 80% in energy cost & Direct replacement and easy to fit

Unique optical design for shadow for illumination unlike multiple LED lamps and Instant On Light

Applications



RECESSED CANS

TRACK LIGHTING

Notes

Available in other color temperature also (upon request) Dimension with +0.1 inch tolerance Lumen maintenance (L70>35,000 hrs.) Specification can be changed without prior notice, as LED is a dynamic & new evolving technology

Download Specification Sheet

